

WO 01/34362 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**METHOD AND DEVICE FOR
COMPRESSION MOULDING A CLOSURE CAP**

The invention concerns a method and a device for compression moulding a container closure cap, which has a first part and a second part, which are joined together by at least one thinner section. For example, a closure
5 cap having a body and a tamper evident band joined together by thin frangible bridges or a closure cap having a body and a lid connected by a thin hinge section.

10 The aim of the invention is to design a method and apparatus so as to guarantee that during compression moulding, the closure cap and in particular the thinner section or sections are formed completely in the mould cavity provided, without it being necessary to insert
15 excess plastics material into the mould, which is then pressed out of the mould upon closing of the mould cavity.

This aim is solved according to the invention with the
20 method defined in Claim 1 and with the apparatus defined in Claim 3 respectively.

Examples of the invention are explained below with reference to the accompanying drawings, in which:

25

Fig. 1 shows a schematic representation of a female mould part and a male mould part of a compression moulding device according to the invention in a closed position.

-2-

Fig. 2 shows the female mould part and the male mould part of Fig. 1 in a final position.

Fig. 3 shows a female mould part and a male mould part of another embodiment of the compression moulding device in a closed position.

Fig. 4 shows the female mould part and the male mould part of Fig. 3 in a final position.

Fig. 5 shows the female mould part and the male mould part of a third embodiment of the compression moulding machine in a closed position and

Fig. 6 shows the female mould part and the male mould part of Fig. 5 in a final position.

Figures 1 and 2 show schematically a female mould part 11 and a male mould part 12, which are axially moveable relative to one another. In their open position (not represented), the female mould part 11 and the male mould part 12 are separated by a distance from one another. A portion of softened plastics material is fed into the female mould part, whilst the mould is in this open position.

The female mould part 11 and the male mould part 12 are then moved relative to one another (by means not represented) into the closed position shown in Fig.1, where a circumferential edge of the male mould part lies on an upper edge of the female mould part. In this position, the female mould part and male mould part define a mould cavity between one another, in the form of a container closure cap. In the position shown in Fig. 1

-3-

the plastics material 13 does not yet fill the mould cavity completely.

An additional mould part 14 is arranged in the female mould part 11. The mould part 14 is moveable relative to the mould cavity by means of a hydraulic ram 15, in order to reduce the volume of the mould cavity, until the plastics material 13 fills the mould cavity completely, as shown in Fig. 2. The finished container closure cap represented in Fig. 2 has a first part in the form of a bottom end 16 and a circumferential wall 17 extending from the bottom end, a second part in the form of an annular element 18 and at least one thinner section 19 joining the two parts together. The mould cavity correspondingly has a first cavity part for forming the first part 16, 17 of the closure cap, a second cavity part for forming the second part 18 of the closure cap and an intermediate cavity part for forming the thinner section 19.

20

After closing the mould cavity, the position shown in Fig. 1, the plastics material (from the portion of plastics material fed in to the mould cavity when the male and female mould parts were in their open position) fills the first cavity part, which forms the first part, 16, 17 of the closure cap. As a rule, the plastics material fills the first cavity part virtually completely, but does not fill or at most partly fills the second cavity part (which forms the second part 18 of the closure cap) and the intermediate cavity part (which forms the thinner section 19). Upon movement of the

30

additional mould part 14 to reduce the volume of the
mould cavity, part of the plastics material is then
pressed out of the first cavity part through the
intermediate cavity part and into the second cavity part,
5 until the plastics material fills the whole mould cavity
completely.

The annular element 18 may be, for example, a tamper
evident band, which is joined to the circumferential wall
10 17 via a thinner section 19 in the form of a
predetermined breaking line or line of weakening, so that
upon the removal of the closure cap from a container the
tamper evident band 18 is separated from the
circumferential wall 17. Such a predetermined breaking
15 line 19 is in a narrow area of the mould cavity, in which
the plastics material is only thin and if necessary also
has openings, so that the line of weakening 19 is defined
by a plurality of thin, frangible bridges.

20 In the example described above, the additional mould
part 14 is arranged in the female mould part 11. However,
the additional mould part (for reducing the volume of the
mould cavity after closing of the same) could also be
arranged, with equal effect in the male mould part 12
25 instead of in the female mould part 11.

The embodiment of the compression moulding device
according to Fig. 3 and 4 contains the same elements as
the device according to Fig. 1 and 2, and these elements
30 are designated with the same reference numbers as in Fig.
1 and 2.

Unlike the device according to Fig. 1 and 2, in the device according to Fig. 3 and 4 a second additional mould part 20 is arranged in the male mould part 12. The second additional mould part 20 is moveable in the male
5 mould part 12 against the action of a force F. In the device according to Fig. 3 and 4, after the mould cavity is closed by the hydraulic ram 15, the first additional mould part 14 is moved into a predetermined final
10 position, reducing the volume of the mould cavity, until the plastics material fills the whole mould cavity completely. The pre-determined final position in the example is defined by a band 21, on the additional mould part 14, knocking against a counter-face 22 (Fig. 3) on the female mould part 11.

15 The second additional mould part 20, is shifted against the action of the force F by the pressure of the plastics material 13, which is produced by the movement of the first additional mould part 14. Thus, the second additional mould part 20 is used for volume equalisation,
20 which means that the final volume of the mould cavity is adapted exactly to the size of the portion of plastics material fed into the mould cavity. The final pressure of the plastics material 13 produced in the mould cavity is controlled by the size of the force F.

25 Through the predetermined final position of the first additional mould part 14 moveable in the female mould 11, the external shape of the closure cap formed, is precisely predetermined, regardless of any deviations from a nominal size occurring in the size of the portion
30 of plastics material fed into the mould cavity.

-6-

The device according to Fig. 5 and 6 again contains the second additional mould part 20 moveable in the male mould part 12 against the action of the force F. The male mould part 12 and a female mould part 111 are axially
5 movable relative to one another. In the closed position represented, a circumferential part of the male mould part 12 lies on an upper edge of the female mould part 111, the male mould part and the female mould part define a mould cavity between one another in the shape of a
10 container closure cap. The female mould part 111 is held such that it can move axially in a holder part 110 and is spring-loaded with regard to the holder part 110 in the final position shown in Fig.5 by means of a compression spring 109.

15 A cylindrical projection 114 of the holder part 110 projects into the female mould part 111 and forms a first additional mould part. The female mould part 111 (and the mould cavity formed therein) and the additional mould part 114 are moveable axially relative to one another
20 against the action of the spring 109, in order to reduce the volume of the mould cavity, until the plastics material 13 fills the whole cavity completely as shown in Fig. 6. This movement takes place through the fact that means (not represented) for closing the mould cavity
25 presses the circumferential part of the male mould part 12 on to the upper edge of the female mould part 111, and moves the female and male mould parts and thereby the mould cavity further together into the holder part 110. After this movement, the mould cavity and the first
30 additional mould part 114 have a predetermined final position relative to one another (Fig. 6), which is

-7-

defined in this example through the fact that a lower edge of the female mould part 111 knocks against a counter-face 122 of the holder part 110.

The purpose and effect of the second additional
5 mould part 20 in the device according to Fig. 5 and 6 are the same as in the device according to Fig. 3 and 4.

CLAIMS

1. A method for compression moulding a container closure cap, which has a first part (16, 17) and a second part (18), which are joined together by at least one thinner section (19), characterised by the following steps:
 - Preparing a mould with a female mould part (11; 111) and a male mould part (12), which are moveable relative to one another, in order to enclose there between a mould cavity, which has a first mould part for forming the first part (16, 17) of the closure cap, a second mould part for forming the second part (18) of the closure cap and an intermediate cavity part for forming the thinner section (19),
 - Feeding a portion of plastics material into the female mould part (11; 111),
 - Moving the female mould part (11; 111) and the male mould part (12) relative to one another to close the mould cavity,
 - Moving an additional mould part (14; 114) relative to the mould cavity in such a way that the volume of the mould cavity is reduced and a part of the portion of plastics material is pressed from the first cavity part through the intermediate cavity part into the second cavity part, in order to form the thinner section (19) and the second part (18) of the closure cap.
2. A method according to Claim 1, for compression moulding a container closure cap, in which the first part (16, 17) defines a bottom end and a

circumferential wall and the second part (18) defines an annular element

3. A device for compression moulding of a container closure cap, which has a first part (16, 17) and a second part (18), which are joined together by at least one thinner section (19), characterised by a female mould part (11; 111) and a male mould part (12), which are moveable relative to one another, in order to enclose a mould cavity, which has a first cavity part for forming the first part (16, 17) of the closure cap, a second cavity part for forming the second part (18) of the closure cap and an intermediate cavity part for forming the thinner section (19), and an additional mould part (14; 114), which after the closing of the mould cavity is moveable relative to the mould cavity, in order to reduce the volume of the mould cavity and to press plastics material (13) out of the first cavity part through the intermediate cavity part into the second cavity part, until the plastics material fills the mould cavity completely.
4. A device according to Claim 3, characterised in that the first cavity part is formed for moulding a bottom end (16) and a circumferential wall (17) of the closure cap and the second cavity part is formed for moulding an annular element (18) of the closure cap.
5. A device according to Claim 4, characterised in that the second cavity part is formed for moulding a tamper evident band (18) and the intermediate cavity part is formed for moulding a nominal breaking line

(19) between the circumferential wall (17) and the tamper evident band (18).

6. A device according to any one of the Claims 3 to 5, characterised by a second additional mould part (20), which after the complete filling of the mould cavity is moveable in response to the pressure of the plastics material (13) in the mould cavity.
7. A device according to Claim 6, characterised in that, after the closing of the mould cavity, the first-mentioned additional mould part (14; 114) is moveable into a predetermined final position.
8. A device according to Claim 6 or 7, characterised in that the first-mentioned additional mould part (14; 114) is moveable axially in the female mould part (11; 111) and the second additional mould part (20) is moveable axially in the male mould part (12).

1/2

Fig.1.




Fig.2.




Fig.3.





Fig.4.



2/2

Fig.5.





Fig.6.



INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/GB 00/04175

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B29C43/36 B65D41/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B29C B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 776 782 A (ISHII OSAMU ET AL) 11 October 1988 (1988-10-11) column 11, line 52 -column 14, line 49; figure 4 ---	1-8
X	US 4 649 013 A (YAMADA MUNEKI ET AL) 10 March 1987 (1987-03-10) column 4, line 14 -column 9, line 68; figures 1-15 ---	1-5,7,8
X	US 5 786 079 A (ALIERI RODIERO) 28 July 1998 (1998-07-28) column 1, line 52-54; figures 1,3-7 column 4, line 37 -column 5, line 5; claim 1 --- -/--	1-5,7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

25 January 2001

Date of mailing of the international search report

02/02/2001

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Foulger, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/04175

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 903 212 A (OWENS ILLINOIS CLOSURE INC) 24 March 1999 (1999-03-24) claim 19; figures 19,20,27B,27C,30,31 ---	1-5
X	US 5 149 479 A (NAKAJIMA HIDEO) 22 September 1992 (1992-09-22)	1,3,7,8
A	the whole document -----	2,4

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/04175

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4776782	A	11-10-1988	JP 1055084 B	22-11-1989
			JP 1567672 C	10-07-1990
			JP 58173612 A	12-10-1983
			EP 0091653 A	19-10-1983
US 4649013	A	10-03-1987	JP 59098812 A	07-06-1984
			AU 545041 B	27-06-1985
			AU 1410683 A	12-01-1984
			CA 1203059 A	15-04-1986
			DE 3369273 D	26-02-1987
			EP 0099171 A	25-01-1984
			KR 8601111 B	13-08-1986
			ZA 8303202 A	27-06-1984
US 5786079	A	28-07-1998	IT 80940410 A	19-03-1996
			AU 3568195 A	09-04-1996
			BR 9506370 A	16-09-1997
			EP 0730520 A	11-09-1996
			JP 9505779 T	10-06-1997
			CA 2176568 A	28-03-1996
			CN 1135734 A	13-11-1996
			WO 9609153 A	28-03-1996
EP 0903212	A	24-03-1999	US 6074583 A	13-06-2000
			AU 8612698 A	01-04-1999
			BR 9803947 A	28-03-2000
			CA 2247590 A	22-03-1999
			CN 1212922 A	07-04-1999
			CZ 9803008 A	14-04-1999
			HU 9802124 A	28-05-1999
			JP 3017177 B	06-03-2000
			JP 11179748 A	06-07-1999
			PL 328760 A	29-03-1999
			ZA 9808626 A	31-03-1999
US 5149479	A	22-09-1992	JP 3254919 A	13-11-1991
			CA 2035921 A	07-09-1991
			DE 4106465 A	12-09-1991
			FR 2659267 A	13-09-1991
			GB 2241663 A, B	11-09-1991